



Armadi refrigerati ventilati GN2/1 serie PREMIUM PREMIUM series ventilated refrigerated GN2/1 cabinets



* Ref.: 2015/1094/UE
** Ref.: 2019/2018/UE

MODELLO / MODEL	CLASSE ENERGETICA / ENERGY CLASS	CLASSE CLIMATICA / CLIMATE CLASS	POTENZA WATT / POWER WATT	ALIMENTAZIONE / POWER SUPPLY	TEMPERATURA °C / TEMPERATURE °C	TIPO REFRIGERANTE / REFRIGERANT	TEMPERATURA / UMIDITÀ MAX. / MAX. TEMP. / HUMIDITY	DIMENSIONI mm / DIMENSIONS mm	DIMENSIONI INTERNE mm / INTERNAL DIMENSIONS mm	CAPACITÀ L. / CAPACITY LL.	PESO NETTO Kg / NET WEIGHT Kg	PESO LORDO Kg / GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm / PACKING DIMENSIONS cm	MODELLO / MODEL
AK652TN	C*	4	255	230/1N/50	-2 +8	R290	+40 °C / 60% HR	740x830x2010h	600x680x1400h	650	121	137	77x87x206h	AK652TN
AK652BT	D*	4	570	230/1N/50	-18 -22	R290	+40 °C / 60% HR	740x830x2010h	600x680x1400h	650	123	139	77x87x206h	AK652BT
AK1412TN	D*	5	430	230/1N/50	-2 +8	R290	+40 °C / 60% HR	1480x830x2010h	1340x680x1400h	1333	185	211	151x87x206h	AK1412TN
AK1412BT	D*	4	780	230/1N/50	-18 -22	R290	+40 °C / 60% HR	1480x830x2010h	1340x680x1400h	1333	187	213	151x87x206h	AK1412BT
AK652TNG	B**	4	265	230/1N/50	-2 +8	R290	+40 °C / 60% HR	740x830x2010h	600x680x1400h	650	121	137	77x87x206h	AK652TNG
AK1412TNG	C**	4	445	230/1N/50	-2 +8	R290	+40 °C / 60% HR	1480x830x2010h	1340x680x1400h	1333	185	211	151x87x206h	AK1412TNG



- Struttura in acciaio inox.
- Refrigerazione ventilata con gruppo incorporato.
- Centralina digitale.
- Cornice di battuta della porta riscaldata anti-condensa.
- Evaporazione automatica dell'acqua di condensa.
- Porta reversibile (solo modelli AK652TN/BT).
- Modelli TNG con porta a doppio vetro con cornice in alluminio.
- Spessore isolamento 70 mm.
- Porta con impugnatura ergonomica.
- Guarnizioni magnetiche facilmente estraibili.
- Cella con angoli arrotondati.
- Luce interna a LED.
- Chiusura porte con chiave.
- Pannelli esterni di fondo e posteriore in acciaio galvanizzato.
- Piedini regolabili in acciaio inox.
- Stainless steel structure.
- Ventilated refrigeration with incorporated refrigeration unit.
- Digital controller.
- Anti-condensation heated door frame.
- Automatic condensation evaporation.
- Reversible door (only AK652TN/BT models).
- TNG models with double glazed door with aluminium frame.
- 70 mm insulation thickness.
- Door with ergonomic handle.
- Easy removable magnetic gaskets.
- Internal rounded edges.
- Internal LED light.
- Doors with key lock.
- External bottom and back panels in galvanized steel.
- Adjustable stainless steel feet.



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AK652TN/BT/TNG	3 griglie plastificate GN2/1 - 3 coppie di guide	3 GN2/1 plastic-coated shelves - 3 pairs of guides
AK1412TN/BT/TNG	6 griglie plastificate GN2/1 - 6 coppie di guide 3 griglie centrali	6 GN2/1 plastic-coated shelves - 6 pairs of guides 3 center shelves

MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE22	Griglia plastificata GN2/1	GN2/1 plastic-coated shelf
GDS22	Coppia di guide inox (escluso AK652TNG)	Stainless steel pair of guides (excluded AK652TNG)
GDS23	Coppia di guide inox (solo AK652TNG)	Stainless steel pair of guides (only AK652TNG)
SHE23	Griglia plastificata centrale (solo AK1412TN / BT / TNG)	Plastic-coated center shelf (only for AK1412TN / BT / TNG)
RBA4	Kit 4 ruote (2 con freno) Montaggio ruote	4 casters kit (2 with brake) Casters installation
	Inversione porta (ove possibile)	Door opening inversion (where possible)
KCP03	Kit conversione pasticceria 60x40 con 11 coppie di guide ad "L" per mod. AK652TN / TNG (montaggio incluso)	60x40 pastry conversion kit with 11 pairs of "L" shaped guides for mod. AK652TN / TNG (installation included)

Armadi refrigerati ventilati GN2/1 Ventilated refrigerated GN2/1 cabinets




- Struttura in acciaio inox.
- Refrigerazione ventilata con evaporatore ad alette trattato anticorrosione.
- Gruppo refrigerante incorporato.
- Centralina digitale.
- Cornice di battuta della porta riscaldata anti-condensa.
- Evaporazione automatica dell'acqua di condensa.
- Porta reversibile (solo modelli AK654TN/BT).
- Spessore isolamento 60 mm.
- Porta con impugnatura ergonomica.
- Guarnizioni magnetiche facilmente estraibili.
- Cella con angoli arrotondati.
- Luce interna a LED.
- Chiusura porte con chiave.
- Pannelli esterni di fondo e posteriore in acciaio galvanizzato.
- Piedini regolabili in acciaio inox.
- Stainless steel structure.
- Ventilated refrigeration with anticorrosion treated evaporator.
- Incorporated refrigeration unit.
- Digital controller.
- Anti-condensation heated door frame.
- Automatic condensation evaporation.
- Reversible door (only AK654TN/BT models).
- 60 mm insulation thickness.
- Door with ergonomic handle.
- Easy removable magnetic gaskets.
- Internal rounded edges.
- Internal LED light.
- Doors with key lock.
- External bottom and back panels in galvanized steel.
- Adjustable stainless steel feet.



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AK654TN / BT	3 griglie plastificate GN2/1 - 3 coppie di guide	3 GN2/1 plastic-coated shelves - 3 pairs of guides
AK1414TN / BT	6 griglie plastificate GN2/1 - 6 coppie di guide	6 GN2/1 plastic-coated shelves - 6 pairs of guides
MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE21	Griglia plastificata GN2/1	GN2/1 plastic-coated shelf
GDS21	Coppia di guide inox	Stainless steel pair of guides
RBA4	Kit 4 ruote (2 con freno) Montaggio ruote	4 casters kit (2 with brake) Casters installation
KCP01	Inversione porta (ove possibile) Kit conversione pasticceria 60x40 con 11 coppie di guide ad "L" per mod. AK654TN (montaggio incluso)	Door opening inversion (where possible) 60x40 pastry conversion kit with 11 pairs of "L" shaped guides for mod. AK654TN (installation included)

* Ref. : 2015/1094/UE

MODELLO MODEL	CLASSE ENERGETICA * ENERGY CLASS *	CLASSE CLIMATICA CLIMATE CLASS	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	TEMPERATURA °C TEMPERATURE °C	TIPO REFRIGERANTE REFRIGERANT	TEMPERATURA / UMITÀ MAX. MAX TEMP. / HUMIDITY	DIMENSIONI mm DIMENSIONS mm	DIMENSIONI INTERNE mm INTERNAL DIMENSIONS mm	CAPACITÀ L CAPACITY LL	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm PACKING DIMENSIONS cm	MODELLO MODEL
AK654TN	D	4	215	230/1N/50	-2 +8	R290	+40 °C / 60% HR	740x830x2010h	624x700x1400h	650	120	135	77x86x207h	AK654TN
AK654BT	D	4	480	230/1N/50	-18 -22	R290	+40 °C / 60% HR	740x830x2010h	624x700x1400h	650	125	140	77x86x207h	AK654BT
AK1414TN	D	4	440	230/1N/50	-2 +8	R290	+40 °C / 60% HR	1480x830x2010h	1360x700x1400h	1333	176	210	151x86x207h	AK1414TN
AK1414BT	D	4	780	230/1N/50	-18 -22	R290	+40 °C / 60% HR	1480x830x2010h	1360x700x1400h	1333	186	211	151x86x207h	AK1414BT



Armadi refrigerati ventilati GN2/1 con porta a vetri Ventilated refrigerated GN2/1 cabinets with glass door



AK654TNG

-2 +8
°C
TEMPERATURE RANGE

B

AK1414TNG

-2 +8
°C
TEMPERATURE RANGE

B



- Struttura in acciaio inox.
- Refrigerazione ventilata con evaporatore ad alette trattato anticorrosione.
- Gruppo refrigerante incorporato.
- Centralina digitale.
- Cornice di battuta della porta riscaldata anti-condensa.
- Evaporazione automatica dell'acqua di condensa.
- Porta non reversibile con doppio vetro e cornice in acciaio.
- Porta con triplo vetro e resistenza anticorrosione nel modello AK654BTG.
- Spessore isolamento 60 mm.
- Porta con impugnatura ergonomica.
- Guarnizioni magnetiche facilmente estraibili.
- Cella con angoli arrotondati.
- Luce interna a LED.
- Chiusura porte con chiave.
- Pannelli esterni di fondo e posteriore in acciaio galvanizzato.
- Piedini regolabili in acciaio inox.

- Stainless steel structure.
- Ventilated refrigeration with anticorrosion treated evaporator.
- Incorporated refrigeration unit.
- Digital controller.
- Anti-condensation heated door frame.
- Automatic condensation evaporation.
- Double glazing non reversible door with steel frame.
- Triple glazing door with heating element in AK654BTG model.
- 60 mm insulation thickness.
- Door with ergonomic handle.
- Easy removable magnetic gasket.
- Internal rounded edges.
- Internal LED light.
- Doors with key lock.
- External bottom and back panels in galvanized steel.
- Adjustable stainless steel feet.



AK654BTG

-18 -22
°C
TEMPERATURE RANGE

D



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AK654TNG / BTG	3 griglie plastificate GN2/1 - 3 coppie di guide	3 GN2/1 plastic-coated shelves - 3 pairs of guides
AK1414TNG	6 griglie plastificate GN2/1 - 6 coppie di guide	6 GN2/1 plastic-coated shelves - 6 pairs of guides

MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE21	Griglia plastificata GN2/1	GN2/1 plastic-coated shelf
GDS21	Coppia di guide inox	Stainless steel pair of guides
RBA4	Kit 4 ruote (2 con freno)	4 casters kit (2 with brake)
	Montaggio ruote	Casters installation
KCP01	Kit conversione pasticceria 60x40 con 11 coppie di guide ad "L" per mod. AK654TNG (montaggio incluso)	60x40 pastry conversion kit with 11 pairs of "L" shaped guides for mod. AK654TNG (installation included)

* Ref.: 2019/2018/LE

MODELLO	CLASSE ENERGETICA *	POTENZA WATT	ALIMENTAZIONE	TEMPERATURA °C	TIPO REFRIGERANTE	TEMPERATURA / UMIDITÀ MAX.	DIMENSIONI mm	DIMENSIONI INTERNE mm	CAPACITÀ L	PESO NETTO Kg	PESO LORDO Kg	DIMENSIONI IMBALLLO cm	MODELLO
MODEL	ENERGY CLASS *	POWER WATT	POWER SUPPLY	TEMPERATURE °C	REFRIGERANT	MAX TEMP. / HUMIDITY	DIMENSIONS mm	INTERNAL DIMENSIONS mm	CAPACITY LL	NET WEIGHT Kg	GROSS WEIGHT Kg	PACKING DIMENSIONS cm	MODEL
AK654TNG	B	215	230/1N/50	-2 +8	R290	+40 °C / 60% HR	740x830x2010h	624x700x1400h	650	130	145	77x86x207h	AK654TNG
AK654BTG	D	495	230/1N/50	-18 -22	R290	+40 °C / 60% HR	740x830x2010h	624x700x1400h	650	143	158	77x86x207h	AK654BTG
AK1414TNG	B	440	230/1N/50	-2 +8	R290	+40 °C / 60% HR	1480x830x2010h	1360x700x1400h	1333	195	220	151x86x207h	AK1414TNG

Armadi refrigerati ventilati 60x80 Ventilated refrigerated 60x80 cabinets



- Struttura in acciaio inox.
- Refrigerazione ventilata con evaporatore ad alette trattato anticorrosione.
- Gruppo refrigerante incorporato.
- Centralina digitale.
- Cornice di battuta della porta riscaldata anti-condensa.
- Evaporazione automatica dell'acqua di condensa.
- Porta reversibile.
- Spessore isolamento 60 mm.
- Porta con impugnatura ergonomica.
- Guarnizione magnetica facilmente estraibile.
- Cella con angoli arrotondati.
- Luce interna a LED.
- Chiusura porta con chiave.
- Pannelli esterni di fondo e posteriore in acciaio galvanizzato.
- Piedini regolabili in acciaio inox.
- Stainless steel structure.
- Ventilated refrigeration with anticorrosion treated evaporator.
- Incorporated refrigeration unit.
- Digital controller.
- Anti-condensation heated door frame.
- Automatic condensation evaporation.
- Reversible door.
- 60 mm insulation thickness.
- Door with ergonomic handle.
- Easy removable magnetic gasket.
- Internal rounded edges.
- Internal LED light.
- Door with key lock.
- External bottom and back panels in galvanized steel.
- Adjustable stainless steel feet.



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AK804TN / BT	10 coppie di guide	10 pairs of guides
AKG804BT	10 griglie plastificate 60x80 cm - 10 coppie di guide	10 60x80 cm plastic-coated shelves - 10 pairs of guides
MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE68	Griglia plastificata 60x80 cm	60x80 cm plastic-coated shelf
GDS68	Coppia di guide inox per AK804TN / BT	Stainless steel pair of guides for AK804TN / BT
GDS68G	Coppia di guide inox per AKG804BT	Stainless steel pair of guides for AKG804BT
RBA4	Kit 4 ruote (2 con freno)	4 casters kit (2 with brake)
	Montaggio ruote	Casters installation
	Inversione porta	Door opening inversion

* Ref.: 2015/1094/UE

MODELLO	CLASSE ENERGETICA *	CLASSE CLIMATICA	POTENZA WATT	ALIMENTAZIONE	TEMPERATURA °C	TIPO REFRIGERANTE	TEMPERATURA / UMIDITÀ MAX.	DIMENSIONI mm	DIMENSIONI INTERNE mm	CAPACITÀ L.	PESO NETTO Kg	PESO LORDO Kg	DIMENSIONI IMBALLO cm	MODELLO
MODEL	ENERGY CLASS *	CLIMATE CLASS	POWER WATT	POWER SUPPLY	TEMPERATURE °C	REFRIGERANT	MAX TEMP. / HUMIDITY	DIMENSIONS mm	INTERNAL DIMENSIONS mm	CAPACITY LL.	NET WEIGHT Kg	GROSS WEIGHT Kg	PACKING DIMENSIONS cm	MODEL
AK804TN	D	4	295	230/1N/50	-2 +8	R290	+40 °C / 60% HR	740x990x2010h	624x845x1390h	733	127	144	77x102x207h	AK804TN
AK804BT	D	4	520	230/1N/50	-18 -22	R290	+40 °C / 60% HR	740x990x2010h	624x845x1390h	733	134	151	77x102x207h	AK804BT
AKG804BT	D	4	520	230/1N/50	-18 -22	R290	+40 °C / 60% HR	740x990x2010h	624x845x1390h	733	159	176	77x102x207h	AKG804BT

Armadio refrigerato ventilato a doppia temperatura GN2/1 Ventilated refrigerated cabinet, double temperature, GN2/1



DOPPIA TEMPERATURA
DOUBLE TEMPERATURE

AK600DTV

▲ TN

-2 +8
°C
TEMPERATURE RANGE

ECO FRIENDLY
REFRIGERANT
R600a

▼ BT

-18 -22
°C
TEMPERATURE RANGE

ECO FRIENDLY
REFRIGERANT
R290



- Struttura in acciaio inox.
- Refrigerazione ventilata con evaporatore ad alette trattato anticorrosione.
- Doppio gruppo refrigerante incorporato.
- Doppia centralina digitale.
- Evaporazione automatica dell'acqua di condensa.
- Spessore isolamento 60 mm.
- Porte non reversibili con impugnature ergonomiche.
- Guarnizioni magnetiche facilmente estraibili.
- Cella con angoli arrotondati.
- Chiusura porte con chiave.
- Pannelli esterni di fondo e posteriore in acciaio galvanizzato.
- Piedini regolabili in acciaio inox.

- Stainless steel structure.
- Ventilated refrigeration with anticorrosion treated evaporator.
- Double incorporated refrigeration unit.
- Double digital controller.
- Automatic condensation evaporation.
- 60 mm insulation thickness.
- Non reversible doors with ergonomic handles.
- Easy removable magnetic gaskets.
- Internal rounded edges.
- Doors with key lock.
- External bottom and back panels in galvanized steel.
- Adjustable stainless steel feet.



DOPPIA TEMPERATURA
DOUBLE TEMPERATURE

AK600DTV

▲ TN

-2 +8
°C
TEMPERATURE RANGE

ECO FRIENDLY
REFRIGERANT
R600a

▼ BT

-18 -22
°C
TEMPERATURE RANGE

ECO FRIENDLY
REFRIGERANT
R290



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AK600DTV	4 griglie plastificate GN2/1 - 4 coppie di guide	4 GN2/1 plastic-coated shelves - 4 pairs of guides
MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE21	Griglia plastificata GN2/1	GN2/1 plastic-coated shelf
GDS21	Coppia di guide inox	Stainless steel pair of guides
RBA4	Kit 4 ruote (2 con freno)	4 casters kit (2 with brake)
	Montaggio ruote	Casters installation

MODELLO MODEL	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	TEMPERATURA °C TEMPERATURE °C	TIPO REFRIGERANTE REFRIGERANT	TEMPERATURA / UMIDITÀ MAX. MAX TEMP. / HUMIDITY	DIMENSIONI mm DIMENSIONS mm	DIMENSIONI INTERNE mm INTERNAL DIMENSIONS mm	CAPACITÀ L. CAPACITY LL	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm PACKING DIMENSIONS cm	MODELLO MODEL
AK600DTV	250 / 300	230/1N/50	-2 +8 / -18 -22	R600a / R290	+40 °C / 60% HR	680x860x1970h	2 x 560x680x560h	225 / 225	150	160	72x88x205h	AK600DTV

Armadi refrigerati statici "Snack" e GN2/1 Static refrigerated Snack and GN2/1 cabinets



- Struttura in acciaio inox.
- Refrigerazione statica con ventilatore per uniformare la temperatura.
- Centralina digitale.
- Cornice di battuta della porta riscaldata anti-condensa.
- Raccolta acqua di condensa con bacinella.
- Sbrinatorio a compressore spento nei modelli TN e FH, manuale nei modelli BT.
- Spessore isolamento 60 mm nei modelli AK604TN/BT/FH e AK1204TN/BT, 50 mm nei modelli AK404TN/BT.
- Porta reversibile (esclusi i modelli AK1204TN/BT).
- Guarnizioni magnetiche facilmente estraibili.
- Cella con angoli arrotondati.
- Luce interna a LED.
- Chiusura porta con chiave.
- Pannelli esterni di fondo e posteriore in acciaio galvanizzato.
- Piedini regolabili in acciaio inox.

- *Stainless steel structure.*
- *Static refrigeration with fan to uniform the temperature.*
- *Digital controller.*
- *Anti-condensation heated door frame.*
- *Condensation water collection with basin.*
- *Defrosting when compressor stopped in TN and FH models, manual in BT models.*
- *60 mm insulation thickness in AK604TN/BT/FH and AK1204TN/BT models, 50 mm in AK404TN/BT models.*
- *Reversible door (AK1204TN/BT models excluded).*
- *Easy removable magnetic gaskets.*
- *Internal rounded edges.*
- *Internal LED light.*
- *Door with key lock.*
- *External bottom and back panels in galvanized steel.*
- *Adjustable stainless steel feet.*



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AK404TN	3 griglie plastificate 530x540 mm - 3 coppie di guide	3 530x540 mm plastic-coated shelves - 3 pairs of guides
AK404BT	3 griglie plastificate 530x540 mm - 3 coppie di guide	3 530x540 mm plastic-coated shelves - 3 pairs of guides
AK604TN	3 griglie plastificate GN2/1 - 3 coppie di guide	3 GN2/1 plastic-coated shelves - 3 pairs of guides
AK604BT	3 griglie plastificate GN2/1 - 3 coppie di guide	3 GN2/1 plastic-coated shelves - 3 pairs of guides
AK604FH (fish)	7 cassette porta pesce 600x400x115 mm 7 coppie di guide	7 600x400x115 mm fish containers 7 pairs of guides
AK1204TN	6 griglie plastificate GN2/1 - 6 coppie di guide	6 GN2/1 plastic-coated shelves - 6 pairs of guides
AK1204BT	6 griglie plastificate GN2/1 - 6 coppie di guide	6 GN2/1 plastic-coated shelves - 6 pairs of guides

MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE55	Griglia plastificata 530x540 mm per AK404TN/BT	530x540 mm plastic-coated shelf for AK404TN/BT
SHE21	Griglia plastificata GN2/1 per AK604TN/BT e AK1204TN/BT	GN2/1 plastic-coated shelf for AK604TN/BT and AK1204TN/BT
GDS55	Coppia di guide inox per AK404TN/BT	Stainless steel pair of guides for AK404TN/BT
GDS21	Coppia di guide inox per AK604TN/BT e AK1204TN/BT	Stainless steel pair of guides for AK604TN/BT and AK1204TN/BT
RBA4	Kit 4 ruote (2 con freno) Montaggio ruote Inversione porta (ove possibile)	4 casters kit (2 with brake) Casters installation Door opening inversion (where possible)

* Ref. 2015/1094/E

MODELLO	CLASSE ENERGETICA *	CLASSE CLIMATICA	POTENZA WATT	ALIMENTAZIONE	TEMPERATURA °C	TIPO REFRIGERANTE	TEMPERATURA / UMIDITÀ MAX.	DIMENSIONI mm	DIMENSIONI INTERNE mm	CAPACITÀ L.	PESO NETTO Kg	PESO LORDO Kg	DIMENSIONI IMBALLO cm	MODELLO
MODEL	ENERGY CLASS *	CLIMATE CLASS	POWER WATT	POWER SUPPLY	TEMPERATURE °C	REFRIGERANT	MAX TEMP. / HUMIDITY	DIMENSIONS mm	INTERNAL DIMENSIONS mm	CAPACITY LL.	NET WEIGHT Kg	GROSS WEIGHT Kg	PACKING DIMENSIONS cm	MODEL
AK404TN	D	4	180	230/1N/50	0 +8	R290	+33 °C / 60% HR	680x710x2010h	560x550x1385h	400	98	115	71x74x215h	AK404TN
AK404BT	E	4	415	230/1N/50	-18 -22	R290	+33 °C / 60% HR	680x710x2010h	560x550x1385h	400	102	119	71x74x215h	AK404BT
AK604TN	D	4	175	230/1N/50	0 +8	R290	+33 °C / 60% HR	680x810x2010h	564x680x1394h	535	108	123	71x84x215h	AK604TN
AK604BT	D	4	420	230/1N/50	-18 -22	R290	+33 °C / 60% HR	680x810x2010h	564x680x1394h	535	117	132	71x84x215h	AK604BT
AK604FH (fish)	D	4	175	230/1N/50	-5 +4	R290	+33 °C / 60% HR	680x810x2010h	564x680x1394h	535	108	123	71x84x215h	AK604FH (fish)
AK1204TN	E	4	350	230/1N/50	0 +8	R290	+33 °C / 60% HR	1340x810x2010h	1220x680x1394h	1156	163	183	137x84x207h	AK1204TN
AK1204BT	E	4	670	230/1N/50	-18 -22	R290	+33 °C / 60% HR	1340x810x2010h	1220x680x1394h	1156	176	196	137x84x207h	AK1204BT

Armagli refrigerati serie AKM AKM series refrigerated cabinets



- Struttura esterna in acciaio verniciato bianco.
- Interno in ABS bianco.
- Refrigerazione a piastra con ventilatore nei modelli "R".
- Refrigerazione statica nei ripiani nei modelli "F".
- Centralina digitale.
- Spessore isolamento 45 mm nei modelli "200R e 400R", 60 mm nel modello "600R" e in tutti i modelli "F".
- Sbrinatorio a compressore spento nei modelli "R".
- Sbrinatorio manuale nei modelli "F".
- Porta reversibile.
- Chiusura porta con chiave.
- Due piedini regolabili per livellamento e due ruote fisse posteriori.

- White painted steel external structure.
- Interior in white ABS.
- Rollbond refrigeration with fan in the "R" models.
- Static cooling integrated into the shelves in the "F" models.
- Digital control unit.
- Insulation thickness 45 mm in the "200R and 400R" models, 60 mm in the "600R" model and in all "F" models.
- Stopcompressor defrost in "R" models.
- Manual defrost in "F" models.
- Reversible door.
- Door lock with key.
- Two adjustable feet for leveling and two fixed rear wheels.



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AKM200R	2 griglie plastificate 505x405mm 1 griglia plastificata 505x220mm	2 plastic-coated shelves 505x405mm 1 plastic-coated shelf 505x220mm
AKM400R	3 griglie plastificate 505x405mm 1 griglia plastificata 505x220mm	3 plastic-coated shelves 505x405mm 1 plastic-coated shelf 505x220mm
AKM600R	3 griglie plastificate 650x525mm 1 griglia plastificata 650x315mm	2 plastic-coated shelves 650x525mm 1 plastic-coated shelf 650x315mm
AKM200F	2 ripiani fissi 480x415mm	2 fixed shelves 480x415mm
AKM400F	6 ripiani fissi 480x415mm	6 fixed shelves 480x415mm
AKM600F	6 ripiani fissi 659x515mm	6 fixed shelves 659x515mm

MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE37	Griglia plastificata 505x405mm (mod. 200R e 400R)	505x405mm plastic-coated shelf (mod. 200R and 400R)
SHE38	Griglia plastificata 650x525mm (mod. 600R) Inversione porta	650x525mm plastic-coated shelf (mod. 600R) Door opening inversion

* Ref. 20151094UE

MODELLO MODEL	CLASSE ENERGETICA * ENERGY CLASS *	CLASSE CLIMATICA CLIMATE CLASS	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	TEMPERATURA °C TEMPERATURE °C	TIPO REFRIGERANTE REFRIGERANT	TEMPERATURA / UMBIDITÀ MAX. MAX TEMP / HUMIDITY	DIMENSIONI mm DIMENSIONS mm	DIMENSIONI INTERNE mm INTERNAL DIMENSIONS mm	CAPACITÀ L. CAPACITY LL	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm PACKING DIMENSIONS cm	MODELLO MODEL
AKM200R	A	4	198	230/1N/50	-2 +10	R600a	+ 33 °C / 60% HR	600x585x850h	510x450x620h	140	40	49	64x65x99h	AKM200R
AKM400R	D	4	300	230/1N/50	-2 +10	R600a	+ 33 °C / 60% HR	600x585x1850h	510x450x1620h	360	64	75	64x65x199h	AKM400R
AKM600R	D	4	442	230/1N/50	-2 +10	R600a	+ 33 °C / 60% HR	777x695x1890h	654x540x1660h	580	86	100	82x75x203h	AKM600R
AKM200F	-	-	302	230/1N/50	< -18	R290	+ 33 °C / 60% HR	600x585x850h	480x474x590h	140	40	49	64x65x99h	AKM200F
AKM400F	-	-	384	230/1N/50	< -18	R290	+ 33 °C / 60% HR	600x585x1850h	480x474x1595h	360	64	75	64x65x199h	AKM400F
AKM600F	-	-	450	230/1N/50	< -18	R290	+ 33 °C / 60% HR	777x695x1890h	659x580x1630h	580	86	100	82x75x203h	AKM600F

Armadi refrigerati serie AKM AKM series refrigerated cabinets



ECO FRIENDLY
R290
REFRIGERANT

MODELLI / MODELS
AKM200R SS
AKM400R SS
AKM600R SS

ECO FRIENDLY
R600a
REFRIGERANT

MODELLI / MODELS
AKM200F SS
AKM400F SS
AKM600F SS

DIGIT
00°C
DIGITAL
CONTROLLER

CE
RoHS

- Struttura esterna in acciaio inox.
- Interno in ABS bianco.
- Refrigerazione a piastra con ventilatore nei modelli "R".
- Refrigerazione statica nei ripiani nei modelli "F".
- Centralina digitale.
- Spessore isolamento 45 mm nei modelli "200R SS e 400R SS", 60 mm nel modello "600R SS" e in tutti i modelli "F".
- Sbrinatorio a compressore spento nei modelli "R".
- Sbrinatorio manuale nei modelli "F".
- Porta reversibile.
- Chiusura porta con chiave.
- Due piedini regolabili per livellamento e due ruote fisse posteriori.

- Stainless steel external structure.
- Interior in white ABS.
- Rollbond refrigeration with fan in the "R" models.
- Static cooling integrated into the shelves in the "F" models.
- Digital control unit.
- Insulation thickness 45 mm in the "200R SS and 400R SS" models, 60 mm in the "600R SS" model and in all "F" models.
- Stop-compressor defrost in "R" models.
- Manual defrost in "F" models.
- Reversible door.
- Door lock with key.
- Two adjustable feet for leveling and two fixed rear wheels.



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AKM200R SS	2 griglie plastificate 505x405mm 1 griglia plastificata 505x220mm	2 plastic-coated shelves 505x405mm 1 plastic-coated shelf 505x220mm
AKM400R SS	3 griglie plastificate 505x405mm 1 griglia plastificata 505x220mm	3 plastic-coated shelves 505x405mm 1 plastic-coated shelf 505x220mm
AKM600R SS	3 griglie plastificate 650x525mm 1 griglia plastificata 650x315mm	2 plastic-coated shelves 650x525mm 1 plastic-coated shelf 650x315mm
AKM200F SS	2 ripiani fissi 480x415mm	2 fixed shelves 480x415mm
AKM400F SS	6 ripiani fissi 480x415mm	6 fixed shelves 480x415mm
AKM600F SS	6 ripiani fissi 659x515mm	6 fixed shelves 659x515mm
MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE37	Griglia plastificata 505x405mm (mod. 200R SS e 400R SS)	505x405mm plastic-coated shelf (mod. 200R SS and 400R SS)
SHE38	Griglia plastificata 650x525mm (mod. 600R SS) Inversione porta	650x525mm plastic-coated shelf (mod. 600R SS) Door opening inversion

* Ref.: 2015/1094/UE

MODELLO / MODEL	CLASSE ENERGETICA * ENERGY CLASS *	CLASSE CLIMATICA CLIMATE CLASS	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	TEMPERATURA °C TEMPERATURE °C	TIPO REFRIGERANTE REFRIGERANT	TEMPERATURA / UMBIDITÀ MAX. MAX TEMP / HUMIDITY	DIMENSIONI mm DIMENSIONS mm	DIMENSIONI INTERNE mm INTERNAL DIMENSIONS mm	CAPACITÀ L. CAPACITY LL	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm PACKING DIMENSIONS cm	MODELLO / MODEL
AKM200R SS	A	4	198	230/1N/50	-2 +10	R600a	+ 33 °C / 60% HR	600x585x850h	510x450x620h	140	40	49	64x65x99h	AKM200R SS
AKM400R SS	D	4	300	230/1N/50	-2 +10	R600a	+ 33 °C / 60% HR	600x585x1850h	510x450x1620h	360	64	75	64x65x199h	AKM400R SS
AKM600R SS	D	4	442	230/1N/50	-2 +10	R600a	+ 33 °C / 60% HR	777x695x1890h	654x540x1660h	580	86	100	82x75x203h	AKM600R SS
AKM200F SS	-	-	302	230/1N/50	< -18	R290	+ 33 °C / 60% HR	600x585x850h	480x474x590h	140	40	49	64x65x99h	AKM200F SS
AKM400F SS	-	-	384	230/1N/50	< -18	R290	+ 33 °C / 60% HR	600x585x1850h	480x474x1595h	360	64	75	64x65x199h	AKM400F SS
AKM600F SS	-	-	450	230/1N/50	< -18	R290	+ 33 °C / 60% HR	777x695x1890h	659x580x1630h	580	86	100	82x75x203h	AKM600F SS

Armagli refrigerati serie AKM AKM series refrigerated cabinets

0 +10
°C
TEMPERATURE RANGE

< -18
°C
TEMPERATURE RANGE

DIGIT
00°C
DIGITAL CONTROLLER

LED
LED LIGHT

70
mm
INSULATION

CE
RoHS

R600a
REFRIGERANT



- Struttura esterna in acciaio verniciato bianco.
 - Interno in ABS bianco.
 - Porta con cornice in alluminio.
 - Luce interna a LED.
 - Centralina digitale.
 - Spessore isolamento 60 mm.
 - Sbrinatorio a compressore spento.
 - Chiusura porta con chiave.
 - Due piedini regolabili per livellamento e due ruote fisse posteriori.
- AKM-RG**
- Doppi vetri.
 - Refrigerazione a piastra con ventilatore.
 - Sbrinatorio a compressore spento.
- AKM-FG**
- Triplo vetro con resistenza anti-appannamento.
 - Refrigerazione statica nei ripiani.
 - Sbrinatorio manuale.

- *White painted steel external structure.*
 - *Interior in white ABS.*
 - *Door with aluminium frame.*
 - *Internal LED light.*
 - *Digital control unit.*
 - *Insulation thickness 60 mm.*
 - *Stop-compressor defrost.*
 - *Door lock with key.*
 - *Two adjustable feet for leveling and two fixed rear wheels.*
- AKM-RG**
- *Double glazed glass.*
 - *Roll-bond refrigeration with fan.*
 - *Stop-compressor defrost.*
- AKM-FG**
- *Triple glazed glass with anti-fog heating element.*
 - *Static cooling integrated into the shelves.*
 - *RManual defrost.*

MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AKM200RG	2 griglie plastificate 505x405mm 1 griglia plastificata 505x220mm	2 plastic-coated shelves 505x405mm 1 plastic-coated shelf 505x220mm
AKM400RG	3 griglie plastificate 505x405mm 1 griglia plastificata 505x220mm	3 plastic-coated shelves 505x405mm 1 plastic-coated shelf 505x220mm
AKM600RG	3 griglie plastificate 650x525mm 1 griglia plastificata 650x315mm	2 plastic-coated shelves 650x525mm 1 plastic-coated shelf 650x315mm
AKM200FG	2 ripiani fissi 480x415mm	2 fixed shelves 480x415mm
AKM400FG	6 ripiani fissi 480x415mm	6 fixed shelves 480x415mm
AKM600FG	6 ripiani fissi 659x515mm	6 fixed shelves 659x515mm
MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE37	Griglia plastificata 505x405mm (mod. 200RG e 400RG)	505x405mm plastic-coated shelf (mod. 200RG and 400RG)
SHE38	Griglia plastificata 650x525mm (mod. 600RG)	650x525mm plastic-coated shelf (mod. 600RG)

*Ref. 2019/2018AE

MODELLO MODEL	CLASSE ENERGETICA * ENERGY CLASS *	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	TEMPERATURA °C TEMPERATURE °C	TIPO REFRIGERANTE REFRIGERANT	TEMPERATURA / UMIDETTÀ MAX. MAX TEMP. / HUMIDITY	DIMENSIONI mm DIMENSIONS mm	DIMENSIONI INTERNE mm INTERNAL DIMENSIONS mm	CAPACITÀ L. CAPACITY LL	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLLO cm PACKING DIMENSIONS cm	MODELLO MODEL
AKM200RG	B	205	230/1N/50	0 +10	R600a	+33 °C / 60% HR	600x585x850h	510x450x620h	140	45	54	64x65x99h	AKM200RG
AKM400RG	B	372	230/1N/50	0 +10	R600a	+33 °C / 60% HR	600x585x1850h	510x450x1620h	360	77	88	64x65x199h	AKM400RG
AKM600RG	B	462	230/1N/50	0 +10	R600a	+33 °C / 60% HR	777x695x1890h	654x540x1660h	580	99	113	82x75x203h	AKM600RG
AKM200FG	B	332	230/1N/50	< -18	R290	+33 °C / 60% HR	600x585x850h	480x474x590h	140	50	59	64x65x99h	AKM200FG
AKM400FG	C	478	230/1N/50	< -18	R290	+33 °C / 60% HR	600x585x1850h	480x474x1595h	360	84	95	64x65x199h	AKM400FG
AKM600FG	C	656	230/1N/50	< -18	R290	+33 °C / 60% HR	777x695x1890h	659x580x1630h	580	110	124	82x75x203h	AKM600FG



Armagli refrigerati serie AKM

AKM series refrigerated cabinets

0 +10
°C
TEMPERATURE RANGE

< -18
°C
TEMPERATURE RANGE

DIGIT
DIGITAL CONTROLLER

LED
LED LIGHT

60
INSULATION

CE
RoHS

R600a
REFRIGERANT



- Struttura esterna in acciaio inox.
 - Interno in ABS bianco.
 - Porta con cornice in alluminio.
 - Luce interna a LED.
 - Centralina digitale.
 - Spessore isolamento 60 mm.
 - Sbrinatorio a compressore spento.
 - Chiusura porta con chiave.
 - Due piedini regolabili per livellamento e due ruote fisse posteriori.
- AKM-RG SS**
- Doppi vetri.
 - Refrigerazione a piastra con ventilatore.
 - Sbrinatorio a compressore spento.
- AKM-FG SS**
- Triplo vetro con resistenza antiappannamento.
 - Refrigerazione statica nei ripiani.
 - Sbrinatorio manuale.

- *Stainless steel external structure.*
 - *Interior in white ABS.*
 - *Door with aluminium frame.*
 - *Internal LED light.*
 - *Digital control unit.*
 - *Insulation thickness 60 mm.*
 - *Stop-compressor defrost.*
 - *Door lock with key.*
 - *Two adjustable feet for leveling and two fixed rear wheels.*
- AKM-RG SS**
- *Double glazed glass.*
 - *Roll-bond refrigeration with fan.*
 - *Stop-compressor defrost.*
- AKM-FG SS**
- *Triple glazed glass with anti-fog heating element.*
 - *Static cooling integrated into the shelves.*
 - *Manual defrost.*

MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AKM200RG SS	2 griglie plastificate 505x405mm 1 griglia plastificata 505x220mm	2 plastic-coated shelves 505x405mm 1 plastic-coated shelf 505x220mm
AKM400RG SS	3 griglie plastificate 505x405mm 1 griglia plastificata 505x220mm	3 plastic-coated shelves 505x405mm 1 plastic-coated shelf 505x220mm
AKM600RG SS	3 griglie plastificate 650x525mm 1 griglia plastificata 650x315mm	2 plastic-coated shelves 650x525mm 1 plastic-coated shelf 650x315mm
AKM200FG SS	2 ripiani fissi 480x415mm	2 fixed shelves 480x415mm
AKM400FG SS	6 ripiani fissi 480x415mm	6 fixed shelves 480x415mm
AKM600FG SS	6 ripiani fissi 659x515mm	6 fixed shelves 659x515mm
MODELLO / MODEL	ACCESSORI	ACCESSORIES
SHE37	Griglia plastificata 505x405mm (mod. 200RG e 400RG)	505x405mm plastic-coated shelf (mod. 200RG and 400RG)
SHE38	Griglia plastificata 650x525mm (mod. 600RG)	650x525mm plastic-coated shelf (mod. 600RG)

*M. 2019/2018/E

MODELLO MODEL	CLASSE ENERGETICA * ENERGY CLASS *	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	TEMPERATURA °C TEMPERATURE °C	TIPO REFRIGERANTE REFRIGERANT	TEMPERATURA / UMIDITÀ MAX. MAX TEMP. / HUMIDITY	DIMENSIONI mm DIMENSIONS mm	DIMENSIONI INTERNE mm INTERNAL DIMENSIONS mm	CAPACITÀ L. CAPACITY LL	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLLO cm PACKING DIMENSIONS cm	MODELLO MODEL
AKM200RG SS	B	205	230/1N/50	0 +10	R600a	+33 °C / 60% HR	600x585x850h	510x450x620h	140	45	54	64x65x99h	AKM200RG SS
AKM400RG SS	B	372	230/1N/50	0 +10	R600a	+33 °C / 60% HR	600x585x1850h	510x450x1620h	360	77	88	64x65x199h	AKM400RG SS
AKM600RG SS	B	462	230/1N/50	0 +10	R600a	+33 °C / 60% HR	777x695x1890h	654x540x1660h	580	99	113	82x75x203h	AKM600RG SS
AKM200FG SS	B	332	230/1N/50	< -18	R290	+33 °C / 60% HR	600x585x850h	480x474x590h	140	50	59	64x65x99h	AKM200FG SS
AKM400FG SS	C	478	230/1N/50	< -18	R290	+33 °C / 60% HR	600x585x1850h	480x474x1595h	360	84	95	64x65x199h	AKM400FG SS
AKM600FG SS	C	656	230/1N/50	< -18	R290	+33 °C / 60% HR	777x695x1890h	659x580x1630h	580	110	124	82x75x203h	AKM600FG SS



Frigo-congelatori a pozzetto serie "CDN" "CDN" series chest chiller-freezers



TEMPERATURA IMPOSTABILE
DA +8 A -24 °C
(frigo o congelatore)
TEMPERATURE MAY BE SET
FROM +8 TO -24 °C
(refrigerator or freezer)

TEMPERATURA IMPOSTABILE
DA +8 A -24 °C
(frigo o congelatore)
TEMPERATURE MAY BE SET
FROM +8 TO -24 °C
(Refrigerator or freezer)

CENTRALINA
DIGITALE
DIGITAL
CONTROLLER



- 3 anni di garanzia sul compressore.
- Struttura esterna in acciaio verniciato bianco.
- Struttura interna in alluminio goffrato (mod. AX650CDN in acciaio verniciato bianco).
- Categoria di congelamento 4 stelle.
- Refrigerazione statica.
- Termometro analogico.
- Centralina digitale.
- Spessore isolamento = 75mm.
- Sbrinatorio manuale con foro interno per drenaggio acqua di sbrinatorio.
- Luce interna a LED
- Autonomia in caso di blackout circa 30 ore nel modello AX100CDN, circa 40 ore negli altri modelli.
- Rulli inferiori per spostare l'apparecchiatura.

- 3 years warranty on the compressor.
- External structure made of white painted steel.
- Internal structure made of embossed aluminium (mod. AX650CDN in white painted steel).
- 4 stars freezing class.
- Static refrigeration.
- Analog thermometer.
- Digital controller.
- Insulation thickness = 75mm.
- Manual defrosting with internal draining hole for defrost water.
- Internal LED light.
- Blackout autonomy of approx. 30 hrs for model AX100CDN and approx. 40 hours for the other models.
- Bottom rollers for moving the equipment.

MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AX100CDN	1 cestello 170x310x175h mm + 1 griglia divisoria interna	1 basket 170x310x175h mm + 1 internal divider grid
AX200CDN	1 cestello 170x310x175h mm + 1 griglia divisoria interna	1 basket 170x310x175h mm + 1 internal divider grid
AX300CDN	1 cestello 170x370x180h mm + 1 griglia divisoria interna	1 basket 170x370x180h mm + 1 internal divider grid
AX400CDN	1 cestello 235x455x205h mm + 1 griglia divisoria interna	1 basket 235x455x205h mm + 1 internal divider grid
AX500CDN	1 cestello 235x455x205h mm + 1 griglia divisoria interna	1 basket 235x455x205h mm + 1 internal divider grid
AX650CDN	2 cestelli 235x455x205h mm + 2 griglie divisorie interne	2 baskets 235x455x205h mm + 2 internal divider grids

* Rif.: 2019/2016/EU
** Rif.: 2019/2018/EU

MODELLO	CLASSE ENERGETICA	POTENZA WATT	ALIMENTAZIONE	TEMPERATURA °C	TIPO REFRIGERANTE	TEMPERATURA / UMIDETTÀ MAX.	DIMENSIONI mm	DIMENSIONI INTERNE mm	CAPACITÀ L.	PESO NETTO Kg	PESO LORDO Kg	DIMENSIONI IMBALLO cm	MODELLO
MODEL	ENERGY CLASS	POWER WATT	POWER SUPPLY	TEMPERATURE °C	REFRIGERANT	MAX TEMP. / HUMIDITY	DIMENSIONS mm	INTERNAL DIMENSIONS mm	CAPACITY LL.	NET WEIGHT Kg	GROSS WEIGHT Kg	PACKING DIMENSIONS cm	MODEL
AX100CDN	E*	105	230/1N/50	+8 -24	R600a	+40 °C 60% HR	574x564x845h	430x380x650h	93	25	33	59x58x100h	AX100CDN
AX200CDN	C**	140	230/1N/50	+8 -24	R600a	+40 °C 60% HR	950x564x845h	800x380x650h	190	32	45	98x58x100h	AX200CDN
AX300CDN	D**	190	230/1N/50	+8 -24	R600a	+40 °C 60% HR	1116x644x845h	970x460x650h	282	39	54	115x67x100h	AX300CDN
AX400CDN	D**	240	230/1N/50	+8 -24	R290	+40 °C 60% HR	1275x740x825h	1120x550x610h	345	52	72	132x77x100h	AX400CDN
AX500CDN	D**	250	230/1N/50	+8 -24	R290	+40 °C 60% HR	1535x740x825h	1380x550x610h	435	58	82	158x77x100h	AX500CDN
AX650CDN	D**	310	230/1N/50	+8 -24	R290	+40 °C 60% HR	1930x720x825h	1785x520x610h	561	75	99	198x77x100h	AX650CDN



Congelatori/refrigeratori a pozzetto con porte a vetri

Chest freezers/chillers with glass doors



AX400CFG



- 3 anni di garanzia sul compressore.
- Doppia modalità di funzionamento: refrigeratore (0 +8 °C) o congelatore (≤ -18 °C).
- Struttura esterna in acciaio verniciato bianco e plastica.
- Struttura interna in acciaio verniciato bianco.
- Porte in vetro curvo temperato con trattamento Low-E di isolamento termico.
- Cornice porte e spigoli in plastica grigia.
- Refrigerazione statica.
- Termometro analogico.
- Termostato manuale.
- Sbrinatorio manuale con foro interno per drenaggio acqua di sbrinatorio.
- Spessore isolamento 70 mm.
- Luce interna a LED con interruttore ON/OFF.
- Chiusura porte con chiave.
- Ruote girevoli (di cui 2 con freno).
- 3 years warranty on the compressor.
- Dual functioning mode: chiller (0 +8 °C) or freezer (≤ -18 °C).
- External structure made of white painted steel and plastic.
- Internal structure made of white painted steel.
- Tempered curved glass doors with Low-E treatment.
- Doors frame and edges in gray plastic.
- Static refrigeration.
- Analog thermometer.
- Manual thermostat.
- Manual defrosting with internal hole for defrost water draining.
- 70 mm insulation thickness.
- Internal LED light with ON/OFF switch.
- Doors with key lock.
- Swivel casters (2 with brake).



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AX300CFG	3 cestelli 220x470x190h mm	3 baskets 220x470x190h mm
AX400CFG	4 cestelli 220x470x190h mm	4 baskets 220x470x190h mm
AX500CFG	5 cestelli 220x470x190h mm	5 baskets 220x470x190h mm
AX600CFG	6 cestelli 220x470x190h mm	6 baskets 220x470x190h mm

*Ril. 2019/2018AE

MODELLO MODEL	CLASSE ENERGETICA * ENERGY CLASS *	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	TEMPERATURA °C TEMPERATURE °C	TIPO REFRIGERANTE REFRIGERANT	TEMPERATURA / UMITÀ MAX. MAX TEMP. / HUMIDITY	DIMENSIONI mm DIMENSIONS mm	DIMENSIONI INTERNE mm INTERNAL DIMENSIONS mm	CAPACITÀ L. CAPACITY LL.	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm PACKING DIMENSIONS cm	MODELLO MODEL
AX300CFG	D	198	230/1N/50	0 +8 / ≤ -18	R290	+35 °C / 75% HR	990x705x875h	840x535x600h	300	57	64	107x76x95h	AX300CFG
AX400CFG	D	214	230/1N/50	0 +8 / ≤ -18	R290	+35 °C / 75% HR	1260x705x875h	1110x535x600h	400	67	76	134x76x95h	AX400CFG
AX500CFG	D	236	230/1N/50	0 +8 / ≤ -18	R290	+35 °C / 75% HR	1530x705x875h	1380x535x600h	500	78	89	161x76x95h	AX500CFG
AX600CFG	D	379	230/1N/50	0 +8 / ≤ -18	R290	+35 °C / 75% HR	1800x705x875h	1650x535x600h	600	81	110	198x77x105h	AX600CFG



Frigo-congelatori a isola Island chiller-freezers



AX500DF
D



D
AX700DF



DUAL COMPRESSOR
C
AX1000DF



AX910DF
D

- Struttura esterna ed interna in acciaio verniciato bianco.
- Spessore isolamento **75mm**.
- Refrigerazione statica.
- Modello AX1000DF con sistema di refrigerazione a due compressori.
- Centralina digitale.
- Doppia modalità di funzionamento: **refrigeratore** (0 +8 °C) o **congelatore** (fino a -26 °C).
- Defrost manuale con piletta di scarico per acqua di sbrinamento sul fondo.
- Porte scorrevoli con vetri curvi temperati con trattamento "Low-E".
- Cestelli inclusi.
- Porta-prezzi incluso.
- Chiusura con chiave (solo modelli AX500DF e AX700DF).
- Illuminazione interna con striscia a LED.
- 6 ruote girevoli (di cui 2 con freno).

- *External and internal structure in white painted steel.*
- *75mm insulation thickness.*
- *Static refrigeration.*
- *Model AX1000DF with dual compressor refrigeration system.*
- *Digital control unit.*
- *Dual functioning mode: **chiller** (0 +8 °C) or **freezer** (down to -26 °C).*
- *Manual defrost with drain for defrost water on the bottom.*
- *Baskets included.*
- *Sliding doors with curved tempered glass with "Low-E" treatment.*
- *Price holder included.*
- *Door lock with key.*
- *Internal lighting with LED strip.*
- *6 swivel casters (2 of which with brake).*

Full optional: baskets and front bumper protection for trolleys included.



MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AX500DF	5 cestelli 210x530x150h mm	5 baskets 210x530x150h mm
AX700DF	6 cestelli 245x530x150h mm	6 baskets 245x530x150h mm
AX910DF	6 cestelli 255x660x150h mm	6 baskets 255x660x150h mm
AX1000DF	8 cestelli 255x660x150h mm	8 baskets 255x660x150h mm

*M.: 2019/2018/18/EE

MODELLO MODEL	CLASSE ENERGETICA * ENERGY CLASS *	POTENZA WATT POWER WATT	ALIMENTAZIONE POWER SUPPLY	TEMPERATURA °C TEMPERATURE °C	TIPO REFRIGERANTE REFRIGERANT	TEMPERATURA / UMITÀ MAX. MAX TEMP. / HUMIDITY	DIMENSIONI mm DIMENSIONS mm	DIMENSIONI INTERNE mm INTERNAL DIMENSIONS mm	CAPACITÀ L CAPACITY LL	PESO NETTO Kg NET WEIGHT Kg	PESO LORDO Kg GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm PACKING DIMENSIONS cm	MODELLO MODEL
AX500DF	D	340	230/1N/50	+8 -26	R290	+30 °C / 60% HR	1475x757x858h	1320x605x610h	500	80	100	153x81x105h	AX500DF
AX700DF	D	535	230/1N/50	+8 -26	R290	+30 °C / 60% HR	2000x757x858h	1840x605x610h	700	105	130	206x81x105h	AX700DF
AX910DF	D	650	230/1N/50	+8 -26	R290	+30 °C / 60% HR	2000x850x850h	1850x695x600h	750	102	145	210x92x102h	AX910DF
AX1000DF	C	890	230/1N/50	+8 -26	R290	+30 °C / 60% HR	2500x850x850h	2345x695x600h	950	139	190	260x92x102h	AX1000DF