



Vetrine pasticceria Tiffany

Tiffany Pastry displays



TIFFANY 930



TIFFANY 1230



TIFFANY 1530



TIFFANY 1830



- Struttura interna ed esterna in acciaio inox, plastica e vetro.
- Refrigerazione ventilata.
- Gruppo refrigerante incorporato.
- Centralina digitale.
- Evaporazione automatica dell'acqua di condensa.
- Vetri a doppia camera.
- Vetro frontale curvo.
- Porte scorrevoli.
- Luce interna a LED su ogni ripiano.
- Ripiani e fondo camera in vetro smontabili.
- Ruote girevoli (di cui 2 con freno).

- *Stainless steel, plastic and glass internal and external structure.*
- *Ventilated refrigeration.*
- *Incorporated refrigeration unit.*
- *Digital controller.*
- *Automatic condensation evaporation.*
- *Double glazed glass.*
- *Curved front glass.*
- *Sliding doors.*
- *Internal LED light on each shelf.*
- *Removable glass shelves and chamber bottom.*
- *Swivel casters (2 with brake).*



*M.: 2019/2018AE

MODELLO	CLASSE ENERGETICA *	POTENZA WATT	ALIMENTAZIONE	TEMPERATURA °C	TIPO REFRIGERANTE	TEMPERATURA / UMIDITÀ MAX.	DIMENSIONI mm	DIMENSIONI RIPIANI mm	CAPACITÀ L.	PESO NETTO Kg	PESO LORDO Kg	DIMENSIONI IMBALLLO cm	MODELLO
MODEL	ENERGY CLASS *	POWER WATT	POWER SUPPLY	TEMPERATURE °C	REFRIGERANT	MAX TEMP. / HUMIDITY	DIMENSIONS mm	SHELVES DIMENSIONS mm	CAPACITY LL	NET WEIGHT Kg	GROSS WEIGHT Kg	PACKING DIMENSIONS cm	MODEL
TIFFANY 930	C	525	230/1N/50	+2 +8	R290	+30 °C / 55% HR	925x680x1420h	1 x 810x250 - 1 x 810x310 - 1 x 810x370 FONDO / BOTTOM 840x360	310	164	175	105x79x165h	TIFFANY 930
TIFFANY 1230	C	540	230/1N/50	+2 +8	R290	+30 °C / 55% HR	1225x680x1420h	1 x 1110x250 - 1 x 1110x310 - 1 x 1110x370 FONDO / BOTTOM 1140x360	420	177	212	135x79x165h	TIFFANY 1230
TIFFANY 1530	C	540	230/1N/50	+2 +8	R290	+30 °C / 55% HR	1525x680x1410h	1 x 1410x250 - 1 x 1410x310 - 1 x 1410x370 FONDO / BOTTOM 1440x360	535	230	264	173x87x162h	TIFFANY 1530
TIFFANY 1830	D	600	230/1N/50	+2 +8	R290	+30 °C / 55% HR	1825x680x1410h	2 x 830x250 - 2 x 830x310 - 2 x 830x370 FONDO / BOTTOM 2 x 840x360	650	250	290	203x87x162h	TIFFANY 1830

Espositori refrigerati per pasticceria Pastry display refrigerators



- Struttura in acciaio e vetro.
- Refrigerazione ventilata.
- Gruppo refrigerante incorporato.
- Centralina digitale.
- Sbrinatorio a compressore spento.
- Doppi vetri.
- Porte con cerniere a destra non reversibile.
- Ripiani interni in vetro regolabili in altezza nei modelli AK100ETR e AK400ETR.
- Griglie cromate regolabili nel mod. AK400ETQ.
- Luce interna a LED con interruttore ON/OFF.
- Ruote girevoli (di cui 2 con freno); piedini nel modello da banco AK100ETR.

- Steel and glass structure.
- Ventilated refrigeration.
- Incorporated refrigeration unit.
- Digital controller.
- Stop-compressor defrost.
- Double glazed glasses.
- Non reversible door with hinges on the right side.
- Height adjustable glass shelves in AK100ETR and AK400ETR models.
- Adjustable chrome-plated shelves in AK400ETQ.
- Internal LED light with ON/OFF switch.
- Swivel casters (2 with brake); countertop AK100ETR model with feet.

MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AK100ETR	3 ripiani in vetro Ø390 mm	3 Ø390 mm glass shelves
AK400ETR	4 ripiani in vetro Ø530 mm	4 Ø530 mm glass shelves
AK400ETQ	4 griglie cromate 535x525 mm	5 chrome-plated shelves 535x525 mm

MODELLO / MODEL	CLASSE ENERGETICA * / ENERGY CLASS *	POTENZA WATT / POWER WATT	ALIMENTAZIONE / POWER SUPPLY	TEMPERATURA °C / TEMPERATURE °C	TIPO REFRIGERANTE / REFRIGERANT	TEMPERATURA / UMIDITÀ MAX. / MAX TEMP. / HUMIDITY	DIMENSIONI mm / DIMENSIONS mm	DIMENSIONI INTERNE mm / INTERNAL DIMENSIONS mm	CAPACITÀ L. / CAPACITY LL	PESO NETTO Kg / NET WEIGHT Kg	PESO LORDO Kg / GROSS WEIGHT Kg	DIMENSIONI IMBALLO cm / PACKING DIMENSIONS cm	MODELLO / MODEL
AK100ETR	C	210	230/1N/50	+2 +8	R600a	+30 °C / 60% HR	480x480x1030h	Ø390x660h	100	50	55	57x57x110h	AK100ETR
AK400ETR	C	460	230/1N/50	+2 +8	R290	+30 °C / 60% HR	695x695x1750h	Ø530x1120h	400	125	135	76x76x190h	AK400ETR
AK400ETQ	B	310	230/1N/50	0 +12	R290	+30 °C / 60% HR	652x652x1873h	595x595x1330h	400	132	165	75x75x202h	AK400ETQ

*Rif. 2019/2018/AUE

Espositori refrigerati da banco Countertop refrigerated display cases



- Struttura in acciaio inox, plastica e vetro.
- Refrigerazione ventilata.
- Gruppo refrigerante incorporato.
- Centralina digitale.
- Evaporazione automatica dell'acqua di condensazione.
- Sbrinatorio a compressore spento.
- Vetro frontale curvo nei modelli "EF".
- Porte scorrevoli sul lato operatore.
- Doppi vetri temperati su tutti i lati.
- Luce interna a LED con interruttore ON/OFF.
- Griglie removibili.

- *Stainless steel, plastic and glass structure.*
- *Ventilated refrigeration.*
- *Incorporated refrigeration unit.*
- *Digital controller.*
- *Automatic condensation evaporation.*
- *Defrosting when compressor stopped.*
- *Curved front glass in "EF" models.*
- *Sliding doors on the operator side.*
- *Double tempered glass on all sides.*
- *Internal LED light with ON/OFF switch.*
- *Removable shelves.*

*Ref.: 2019/2018AE

MODELLO / MODEL	CLASSE ENERGETICA * / ENERGY CLASS *	POTENZA WATT / POWER WATT	ALIMENTAZIONE / POWER SUPPLY	TEMPERATURA °C / TEMPERATURE °C	TIPO REFRIGERANTE / REFRIGERANT	TEMPERATURA / UMGIDITÀ MAX. / MAX TEMP. / HUMIDITY	DIMENSIONI mm / DIMENSIONS mm	DIMENSIONI INTERNE mm / INTERNAL DIMENSIONS mm	CAPACITÀ L. / CAPACITY Lt.	PESO NETTO Kg / NET WEIGHT Kg	PESO LORDO Kg / GROSS WEIGHT Kg	DIMENSIONI IMBALLLO cm / PACKING DIMENSIONS cm	MODELLO / MODEL
AK102EF	C	160	230/1N/50	0 +12	R600a	+30 °C / 55% HR	710x467x676h	-	100	57	74	81x53x74h	AK102EF
AK120EF	B	160	230/1N/50	0 +12	R600a	+30 °C / 55% HR	696x568x686h	-	120	57	66	78x63x84h	AK120EF
AK160EF	B	160	230/1N/50	0 +12	R600a	+30 °C / 55% HR	874x568x686h	-	160	59	69	96x63x84h	AK160EF
AK205EF	C	360	230/1N/50	0 +12	R290	+30 °C / 55% HR	1219x568x686h	-	205	89	94	128x62x86h	AK205EF
AK120EFQ	C	160	230/1N/50	0 +12	R600a	+30 °C / 55% HR	702x568x686h	665x465x410h	120	57	67	78x63x86h	AK120EFQ
AK160EFQ	C	160	230/1N/50	0 +12	R600a	+30 °C / 55% HR	880x568x686h	843x465x410h	160	59	70	95x63x86h	AK160EFQ
AK205EFQ	B	360	230/1N/50	0 +12	R290	+30 °C / 55% HR	1219x568x686h	1180x485x370h	242	89	94	128x62x86h	AK205EFQ





Espositori refrigerati da banco e per Tapas Countertop refrigerated display cases and Tapas



Espositori refrigerati da banco

- Struttura interna ed esterna in acciaio inox e vetro.
- Refrigerazione ventilata.
- Gruppo refrigerante incorporato nella parte superiore dell'espositore.
- Centralina digitale.
- Porte scorrevoli sul lato operatore.
- Doppi vetri temperati su tutti i lati, porte comprese.
- Luce interna a LED con interruttore ON/OFF.

Countertop refrigerated display cases

- Stainless steel and glass internal and external structure.
- Ventilated refrigeration.
- Incorporated refrigeration unit on the upper side of the display case.
- Digital controller.
- Sliding doors on the operator side.
- Double tempered glass on all sides, including doors.
- Internal LED light with ON/OFF switch.

Espositori refrigerati per tapas

- Struttura interna ed esterna in vetro, plastica e acciaio inox.
- Refrigerazione nella sola parte inferiore della vetrina (vano vaschette GN).
- Refrigerazione statica.
- Gruppo refrigerante incorporato.
- Centralina digitale.
- Porte scorrevoli sul lato operatore.
- Vetri temperati.
- Ripiano intermedio in vetro.
- Luce interna a LED con interruttore ON/OFF.
- Bacinelle GN h4 cm incluse.

Tapas refrigerated showcases

- Stainless steel, plastic and glass internal and external structure.
- Refrigeration in the lower part of the showcase only (GN pans compartment).
- Static refrigeration.
- Incorporated refrigeration unit.
- Digital controller.
- Sliding doors on the operator side.
- Tempered glass.
- Glass middle shelf.
- Internal LED light with ON/OFF switch.
- GN pans h4 cm included.

*M.: 2019/2018/AE

MODELLO / MODEL	DOTAZIONE STANDARD	STANDARD EQUIPMENT
AK100DR	2 griglie in acciaio cromato 675x325 mm	2 675x325 mm chromed steel shelves
AK180DR	2 griglie in acciaio cromato 675x325 mm	2 675x325 mm chromed steel shelves

MODELLO / MODEL	CLASSE ENERGETICA * / ENERGY CLASS *	POTENZA WATT / POWER WATT	ALIMENTAZIONE / POWER SUPPLY	TEMPERATURA °C / TEMPERATURE °C	TIPO REFRIGERANTE / REFRIGERANT	TEMPERATURA / UMIDITÀ MAX. / MAX TEMP. / HUMIDITY	DIMENSIONI mm / DIMENSIONS mm	DIMENSIONI INTERNE mm / INTERNAL DIMENSIONS mm	CAPACITÀ / CAPACITY	PESO NETTO Kg / NET WEIGHT Kg	PESO LORDO Kg / GROSS WEIGHT Kg	DIMENSIONI IMBALLLO cm / PACKING DIMENSIONS cm	MODELLO / MODEL
AK100DR	C	350	230/1N/50	0 +12	R290	+30 °C / 55% HR	805x438x769h	755x365x435h	101 L.	65	75	90x54x80h	AK100DR
AK180DR	C	350	230/1N/50	0 +12	R290	+30 °C / 55% HR	805x438x969h	755x365x635h	177 L.	77	87	90x54x100h	AK180DR
AK413VTB	C	160	230/1N/50	0 +12	R600a	+25 °C / 60% HR	1135x395x375h	-	4 x GN1/3 h4 cm	39	49	119x47x55h	AK413VTB
AK513VTB	C	160	230/1N/50	0 +12	R600a	+25 °C / 60% HR	1310x395x375h	-	5 x GN1/3 h4 cm	43	55	137x47x55h	AK513VTB
AK613VTB	C	160	230/1N/50	0 +12	R600a	+25 °C / 60% HR	1485x395x375h	-	6 x GN1/3 h4 cm	47	59	154x47x55h	AK613VTB
AK813VTB	C	160	230/1N/50	0 +12	R600a	+25 °C / 60% HR	1755x395x375h	-	8 x GN1/3 h4 cm	53	66	181x47x55h	AK813VTB